TWO ESSENTIAL WORKSHOP TOOLS IN ONE MACHINE!



Every workshop needs a jointer and a planer (Planer/ Thicknesser) in order to produce accurately dimensioned boards. With Wood-Mizer's MP160 Jointer/Plan er (Planer/Thicknesser), you get both in one efficient and compact machine! Take your bowed or cupped rough sawn timber and get it in perfect shape for whatever project you have in mind.

The MP160 efficiently shares one horizontal cutter between two cast iron tables - the upper table for jointing (planing) and the lower table for planing

TOP 3

BENEFITS

4 step process to produce square & straight material

For producers of furniture, windows, doors and more

Use jointer & planer without any setup between modes

(thicknessing). No alterations are needed to switch between jointing (planing) and planing (thicknessing) switch between the two functions easily without stopping the cutter or extractor. You start by using the top table for jointing (planing) - making two adjoining sides perfectly flat and at a precise right angle to each other. You manually advance the board over the cutter by hand. Then you use the bottom table for planing (thicknessing) the last two sides to be parallel to the first two, thicknessing the board to its final dimensions.

A safety guard keeps your hands safe during jointing (planing). The board fence tilts up to 45 degrees for jointing angled boards. The top and bottom tables can be adjusted as needed, and the infeed and outfeed tables always remain parallel to each other. The outfeed table can be fine-adjusted. Two power rollers pull your board under the cutter. The power feed has an industrial gearbox.

The MP160 is all you need to produce furniture-grade timber.

SPECIFICATIONS

CAPACITY

Planer width
Planer table length
Planer, chip thickness Planer fence Thicknesser width Thicknesser width Thicknesser, table lengt Thicknesser, table lengt Thicknesser, chip thickn Horizontal cutter diame Spindle speed Feed roller diameter Feed speed Planetary oper for Planetary gear for

630 mm 4 mm 72 mm 5600 rpm 32 mm 5 m/min 2-12 m/mln

260 mm

630 mm

8 mm 152 x 1100 mm

step less feeding WER FEED

3 kW (4 HP), 3-phase 2.2 kW (3 HP), 1-phase 0.18 kW (0.25 HP), 3-phase 0.37 kW (0.5 HP), 3-pha



ACCESSORIES

Planer blades HSS 410 mm

Planer blades HM 410 mm

Indexable blades

Wedges for profile blades

Extension tables on thicknesser table MP160

4-blades horizontal cutter

Planetary gear for stepless feeding between 2-12 m/min

Indexable blades with holder

DIMENSIONS AND WEIGHT

Length x Width 1040 mm x 720 mm Height Weight 195 kg (Shipping Weight - 220 kg)

